




## NUMINOS® PD PHASE L

Indoor LED pendant light white/black 3000K 24°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® PD PHASE L pendant light, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The pendant light can convince with a power consumption of 28 watts, luminous flux of 2430 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.:	1004350
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700mA
Pendant length	250 cm
Height	21.3 cm
Diameter	10 cm
Net weight	1.2 kg
Gross weight	1.284 kg
Safety class	I
Assembly	Surface
Assembly details	Ceiling, Ceiling with Acc.
Dimmable	Yes
Dimming technology	trailing edge
Wattage	28 W
Lumen	2430 lm
Colour temperature	3000 Kelvin
Beam angle	24 °
Color	white
CRI	90
UGR ≤	13
LXXBXX data	L80B50
BIG WHITE Page	92

## Light Source

791822	
--------	---

## Accessories

1006169	NUMINOS® L , white front ring
---------	----------------------------------