


NUMINOS® PD DALI S

Indoor LED pendant light white/black 3000K 60°

The NUMINOS light system from SLV skilfully combines function, design and technology. With a variety of downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® PD DALI S pendant light, which convinces with the best workmanship and lighting quality. With the spotlight, you can opt for spot lighting or high-quality illumination of larger areas. The pendant light has a power consumption of 10.42 watts, a luminous flux of 1020 lumens, a colour temperature of 3000 Kelvin and a good colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| | |
|-------------------------------------|----------------------------|
| Item no.: | 1004448 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 250mA |
| Pendant length | 250 cm |
| Height | 16.2 cm |
| Diameter | 6.5 cm |
| Net weight | 0.887 kg |
| Gross weight | 1.117 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling, Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | DALI |
| Wattage | 10.42 W |
| Lumen | 1020 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 60 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 19 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 88 |

Light Source

| | |
|--------|---|
| 791815 |  The logo consists of the letters 'A' and 'G' stacked vertically on the left, and a yellow arrow pointing to the right containing the letter 'E' on the right. |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|