




3~ NUMINOS® DALI M

3 phase system light white/black 2700K 24 $^{\circ}$

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the 3~ NU-MINOS® DALI M 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1925 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| Item no.: | 1004462 |
|--|------------------------|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary volta- ge | 500mA |
| Length | 18.5 cm |
| Height | 16.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.83 kg |
| Gross weight | 1.13 kg |
| Safety class | I |
| Assembly details | Track Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Wattage | 20.1 W |
| Lumen | 1925 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 24° |
| Color | white |
| CRI | 90 |
| UGR≤ | 16 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 64 |
| | |



Light Source

| 791800 | A E |
|-------------|-------------------------------|
| Accessories | |
| 1006168 | NUMINOS® M , white front ring |