




3~ NUMINOS® PHASE M

3 phase system light black/black 3000K 60°

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the 3~ NUMINOS® DALI M 3-phase system light LED, which convinces with best workmanship and light quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1880 lumens, colour temperature of 3000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| Item no.: | 1004468 |
|-------------------------------------|------------------------|
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500mA |
| Length | 18.5 cm |
| Height | 16.5 cm |
| Diameter | 8.5 cm |
| Net weight | 0.83 kg |
| Gross weight | 1.13 kg |
| Safety class | I |
| Assembly details | Track Ceiling |
| Dimmable | Yes |
| Dimming technology | DALI |
| Wattage | 20.1 W |
| Lumen | 1880 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 60 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 22 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 64 |
| | |



Light Source

| 791822 | A E |
|-------------|-------------------------------|
| Accessories | |
| 1006168 | NUMINOS® M , white front ring |