


## 3~ NUMINOS® DALI M

### 3 phase system light black/black 4000K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you provide a thousand lighting design options. Like with the 3~ NUMINOS® DALI M 3-phase system light LED, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 2060 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When do you choose NUMINOS® from SLV?



## TECHNICAL DATA

|                                     |                        |
|-------------------------------------|------------------------|
| Item no.:                           | 1004476                |
| Primary nominal voltage             | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500mA                  |
| Length                              | 18.5 cm                |
| Height                              | 16.5 cm                |
| Diameter                            | 8.5 cm                 |
| Net weight                          | 0.83 kg                |
| Gross weight                        | 1.13 kg                |
| Safety class                        | I                      |
| Assembly details                    | Track Ceiling          |
| Dimmable                            | Yes                    |
| Dimming technology                  | DALI                   |
| Wattage                             | 20.1 W                 |
| Lumen                               | 2060 lm                |
| Colour temperature                  | 4000 Kelvin            |
| Beam angle                          | 60 °                   |
| Color                               | black                  |
| CRI                                 | 90                     |
| UGR ≤                               | 25                     |
| LXXBXX data                         | L80B50                 |
| BIG WHITE Page                      | 64                     |

## Light Source

|        |  |
|--------|--|
| 791825 |  The logo consists of the letters 'A' and 'G' stacked vertically in a small square, followed by a yellow arrow pointing to the right containing the letter 'E'. |
|--------|--|

## Accessories

|         |                               |
|---------|-------------------------------|
| 1006168 | NUMINOS® M , white front ring |
|---------|-------------------------------|