




NUMINOS® SPOT DALI

Indoor LED recessed ceiling light white/black 2700K 60°

The NUMINOS light system from SLV perfectly combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Like with the NUMINOS® SPOT DALI M indoor ceiling-mounted light LED, which impresses with its high-quality workmanship and light. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The recessed ceiling light convinces with a power consumption of 20.1 watts, luminous flux of 1885 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| Primary nominal voltage Secondary power / secondary voltage Length 18.5 cm Height 16.5 cm Diameter Net weight Gross weight 1.19 kg Safety class I Assembly Assembly details Dimmable Dimmable Ves Dimming technology Wattage Lumen Colour temperature Beam angle Color Soundary power / secondary voltage 500mA 500mA 500mA 500mA 500mA 500mA 500mA 60 colon Color Soundary power / secondary voltage 500mA 500mA 500mA 60 color 500mA 60 color 500mA 60 color Surface Color Surface 220.1 W Lumen Colour temperature 60 color White | Item no.: | 1004488 |
|---|-------------------------------------|------------------------|
| Length 18.5 cm Height 16.5 cm Diameter 8.5 cm Net weight 0.89 kg Gross weight 1.19 kg Safety class I Assembly Surface Assembly details Ceiling Dimmable Yes Dimming technology DALI Wattage 20.1 W Lumen 1885 lm Colour temperature 2700 Kelvin Beam angle 60 ° | Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Height 16.5 cm Diameter 8.5 cm Net weight 0.89 kg Gross weight 1.19 kg Safety class I Assembly Surface Assembly Ceiling Dimmable Yes Dimming technology DALI Wattage 20.1 W Lumen 1885 lm Colour temperature 2700 Kelvin Beam angle 60 ° | Secondary power / secondary voltage | 500mA |
| Diameter8.5 cmNet weight0.89 kgGross weight1.19 kgSafety classIAssemblySurfaceAssembly detailsCeilingDimmableYesDimming technologyDALIWattage20.1 WLumen1885 lmColour temperature2700 KelvinBeam angle60 ° | Length | 18.5 cm |
| Net weight 0.89 kg Gross weight 1.19 kg Safety class I Assembly Surface Assembly details Ceiling Dimmable Yes Dimming technology DALI Wattage 20.1 W Lumen 1885 lm Colour temperature 2700 Kelvin Beam angle 60 ° | Height | 16.5 cm |
| Gross weight 1.19 kg Safety class I Assembly Surface Ceiling Dimmable Yes Dimming technology DALI Wattage Lumen 1885 Im Colour temperature 2700 Kelvin Beam angle | Diameter | 8.5 cm |
| Safety class Assembly Surface Ceiling Dimmable Yes Dimming technology DALI Wattage Lumen 1885 Im Colour temperature 2700 Kelvin Beam angle | Net weight | 0.89 kg |
| Assembly Surface Assembly details Ceiling Dimmable Yes Dimming technology DALI Wattage 20.1 W Lumen 1885 Im Colour temperature 2700 Kelvin Beam angle 60 ° | Gross weight | 1.19 kg |
| Assembly details Ceiling Dimmable Yes Dimming technology DALI Wattage 20.1 W Lumen 1885 Im Colour temperature 2700 Kelvin Beam angle 60 ° | Safety class | I |
| DimmableYesDimming technologyDALIWattage20.1 WLumen1885 lmColour temperature2700 KelvinBeam angle60 ° | Assembly | Surface |
| Dimming technology Wattage 20.1 W Lumen 1885 Im Colour temperature 2700 Kelvin Beam angle 60 ° | Assembly details | Ceiling |
| Wattage 20.1 W Lumen 1885 Im Colour temperature 2700 Kelvin Beam angle 60 ° | Dimmable | Yes |
| Lumen 1885 Im Colour temperature 2700 Kelvin Beam angle 60 ° | Dimming technology | DALI |
| Colour temperature 2700 Kelvin Beam angle 60 ° | Wattage | 20.1 W |
| Beam angle 60 ° | Lumen | 1885 lm |
| | Colour temperature | 2700 Kelvin |
| Color white | Beam angle | 60 ° |
| | Color | white |
| CRI 90 | CRI | 90 |
| UGR ≤ 22 | UGR≤ | 22 |
| LXXBXX data L80B50 | LXXBXX data | L80B50 |
| BIG WHITE Page 74 | BIG WHITE Page | 74 |



Light Source

| 791800 | A E |
|-------------|-------------------------------|
| Accessories | |
| 1006168 | NUMINOS® M , white front ring |