




NUMINOS® PD DALI M

Indoor LED pendant light black/black 3000K 60°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. Like with the NUMINOS® PD DALI M pendant light, which impresses with its high-quality workmanship and light. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The pendant light can convince with a power consumption of 20.1 watts, luminous flux of 1880 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|-------------------------------------|----------------------------|
| Item no.: | 1004540 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 500mA |
| Pendant length | 250 cm |
| Height | 18.5 cm |
| Diameter | 8.5 cm |
| Net weight | 1.181 kg |
| Gross weight | 1.339 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling, Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | DALI |
| Wattage | 20.1 W |
| Lumen | 1880 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 60 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 90 |

Light Source

| | |
|--------|--|
| 791822 | |
|--------|--|

Accessories

| | |
|---------|-------------------------------|
| 1006168 | NUMINOS® M , white front ring |
|---------|-------------------------------|