




NUMINOS® PD DALI L

Indoor LED pendant light black/black 2700K 60°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® PD DALI L pendant light, which convinces with the best workmanship and lighting quality. In this way, you can create high-quality illumination of larger areas or use the spotlight for selective lighting. The pendant light can convince with a power consumption of 28 watts, luminous flux of 2475 lumens, colour temperature of 2700 Kelvin and a high colour reproduction index of over 90. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| | |
|-------------------------------------|----------------------------|
| Item no.: | 1004628 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 700mA |
| Pendant length | 250 cm |
| Height | 21.3 cm |
| Diameter | 10 cm |
| Net weight | 1.456 kg |
| Gross weight | 1.743 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling, Ceiling with Acc. |
| Dimmable | Yes |
| Dimming technology | DALI |
| Wattage | 28 W |
| Lumen | 2475 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 60 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |
| LXXBXX data | L80B50 |
| BIG WHITE Page | 92 |

Light Source

| | |
|--------|---|
| 791800 |  The logo consists of the letters 'A' and 'G' stacked vertically on the left, and a yellow arrow pointing to the right containing the letter 'E' on the right. |
|--------|---|

Accessories

| | |
|---------|-------------------------------|
| 1006169 | NUMINOS® L , white front ring |
|---------|-------------------------------|