



## NUMINOS® MOVE S

white recessed ceiling light, 3000K 20°

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® MOVE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



### TECHNICAL DATA

|                                     |             |
|-------------------------------------|-------------|
| Item no.:                           | 1005347     |
| Number of different light outlets   | 1           |
| Secondary power / secondary voltage | 250mA       |
| Height                              | 6.35 cm     |
| Diameter                            | 10 cm       |
| Installation diameter               | 9 cm        |
| Installation depth                  | 8.5 cm      |
| Net weight                          | 0.19 kg     |
| Gross weight                        | 0.203 kg    |
| IP Code                             | IP 20       |
| Safety class                        | III         |
| Impact resistance class             | IK02        |
| Impact resistance                   | 0,2 Joule   |
| Assembly                            | Recessed    |
| Assembly details                    | Ceiling     |
| Wattage                             | 8.6 W       |
| Lumen                               | 730 lm      |
| Colour temperature                  | 3000 Kelvin |
| Beam angle                          | 20 °        |
| Color                               | white       |
| CRI                                 | 90          |
| UGR ≤                               | 19          |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791815 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                          |
|---------|----------------------------------------------------------|
| 1004055 | LED driver , 6.5-10W<br>250mA PHASE                      |
| 1004058 | LED driver , 6.5-10W<br>250mA                            |
| 1004067 | LED driver , 15W 250mA<br>DALI                           |
| 1004786 | NUMINOS® S , diffuser<br>Ellipse                         |
| 1004787 | NUMINOS® S , diffuser<br>Prisma                          |
| 1004788 | NUMINOS® S , diffuser<br>Frosted                         |
| 1004789 | NUMINOS® S , diffuser<br>Wabe                            |
| 1006139 | Numinos® S Mounting<br>Frame , round<br>160/100mm black  |
| 1006140 | Numinos® S Mounting<br>Frame , round<br>160/100mm white  |
| 1006141 | Numinos® S Mounting<br>Frame , square<br>160/100mm black |
| 1006142 | Numinos® S Mounting<br>Frame , square<br>160/100mm white |

|                             |        |
|-----------------------------|--------|
| LXXBXX data                 | L80B50 |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C  |
| BIG WHITE Page              | 41     |