




MILANDOS 4

white recessed ceiling light, 2700K 45°

The MILANDOS recessed ceiling light convinces with its compact design and innovative lighting properties. It shines above all with a true-to-life colour reproduction index of over 90 out of 60,000. With a UGR of 23, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends stylishly into any room. The spotlight is also quick and easy to install. Experience light with SLV – your reliable partner for all kinds of indoor lights for 40 years.



TECHNICAL DATA

Item no.:	1005409
Secondary power / secondary voltage	700mA
Length	13.6 cm
Width	5.6 cm
Height	4.3 cm
Installation length	13 cm
Installation width	4.9 cm
Installation depth	7 cm
Net weight	0.25 kg
Gross weight	0.268 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling
Lumen	640 lm
Colour temperature	2700 Kelvin
Beam angle	45 °
Color	white
CRI	90
UGR ≤	23
LXXBXX data	L80B50

Light Source

916372	
--------	---

Accessories

1002423	LED driver MEDO 300 , dimmable DALI/1-10V
464142	LED DRIVER , 10.5W, 700mA, incl. strain relief, dimmable

Ambient temperature	30 °C
BIG WHITE Page	349