


MILANDOS 8

black recessed ceiling light, 2700K 45°

The MILANDOS recessed ceiling light convinces with its compact design and innovative lighting properties. It shines above all with a true-to-life colour reproduction index of over 90 out of 60,000. With its simple design, the square recessed ceiling light made of aluminium and polycarbonate (PC) blends stylishly into any room. With a UGR of 16, it conjures up a high-quality, glare-free light. The spotlight is also quick and easy to install. When will you test out the benefits of SLV's impressive indoor lights?



TECHNICAL DATA

Item no.:	1005423
Secondary power / secondary voltage	700mA
Length	25.6 cm
Width	5.6 cm
Height	4.3 cm
Installation length	25 cm
Installation width	4.9 cm
Installation depth	7 cm
Net weight	0.4 kg
Gross weight	0.428 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling
Lumen	1030 lm
Colour temperature	2700 Kelvin
Beam angle	45 °
Color	black
CRI	90
UGR ≤	16
LXXBXX data	L80B50

Light Source

916372	
--------	--

Accessories

1002423	LED driver MEDO 300 , dimmable DALI/1-10V
1006202	LED Driver , 20W 700mA

Ambient temperature	30 °C
BIG WHITE Page	349