


MILANDOS 8

white recessed ceiling light, 3000K 45°

Minimalist, compact and innovative, the MILANDOS recessed ceiling light convinces with its lighting properties. The long LED lifespan of 60,000 hours and the high colour reproduction index of over 90 are also convincing across the board. With a UGR of 23, it produces glare-free light. The simple design of the recessed ceiling light made of aluminium and polycarbonate (PC) blends stylishly into any room. The spotlight is also quick and easy to install. Experience MILANDOS in action and convince yourself of a successful lighting experience.



TECHNICAL DATA

Item no.:	1005426
Secondary power / secondary volta- ge	700mA
Length	25.6 cm
Width	5.6 cm
Height	4.3 cm
Installation length	25 cm
Installation width	4.9 cm
Installation depth	7 cm
Net weight	0.4 kg
Gross weight	0.428 kg
IP Code	IP 20
Safety class	111
Safety class Impact resistance class	IK02
Impact resistance class	IK02
Impact resistance class Assembly	IK02 Recessed
Impact resistance class Assembly Assembly details	IK02 Recessed Ceiling
Impact resistance class Assembly Assembly details Lumen	IK02 Recessed Ceiling 1300 Im
Impact resistance class Assembly Assembly details Lumen Colour temperature	IK02 Recessed Ceiling 1300 lm 3000 Kelvin
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle	IK02 Recessed Ceiling 1300 Im 3000 Kelvin 45 °
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle Color	IK02 Recessed Ceiling 1300 Im 3000 Kelvin 45 ° white
Impact resistance class Assembly Assembly details Lumen Colour temperature Beam angle Color	IK02 Recessed Ceiling 1300 Im 3000 Kelvin 45 ° white



Light Source

916414	A E
Accessories	
1002423	LED driver MEDO 300 , dimmable DALI/1-10V
1006202	LED Driver , 20W 700mA

Ambient temperature	30 °C
BIG WHITE Page	349