




NUMINOS® XS

black recessed ceiling light, 2700K 40°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| Item no.: | 1005502 |
|--|---------------|
| Secondary power / secondary volta- ge | 200mA |
| Height | 4.5 cm |
| Diameter | 6.5 cm |
| Installation diameter | 5.5 cm |
| Installation depth | 11 cm |
| Net weight | 0.09 kg |
| Gross weight | 0.096 kg |
| IP Code | IP 20 / IP 44 |
| Safety class | 111 |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 7 W |
| Lumen | 620 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 40 ° |
| Color | black |
| CRI | 90 |
| UGR≤ | 22 |
| LXXBXX data | L80B50 |
| | |



Light Source

| 798300 | | Minimum ambient temperature | -20 °C |
|-------------|---|-----------------------------|--------|
| Accessories | | Maximum ambient temperature | 40 °C |
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector | BIG WHITE Page | 29 |
| 1005610 | LED Driver , 200mA 10- W, Quick Connector | | |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector | | |
| 1005612 | NUMINOS® XS , diffuser | | |
| 1005613 | NUMINOS® XS , trans- parent diffuser | | |
| 1005614 | NUMINOS® XS , frosted diffuser | | |
| 1005615 | NUMINOS® XS , black diffuser | | |