




## **NUMINOS® XS**

## black / chrome recessed ceiling light, 2700K $40^{\circ}$

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## **TECHNICAL DATA**

Item no.:	1005504
Secondary power / secondary volta- ge	200mA
Height	4.5 cm
Diameter	6.5 cm
Installation diameter	5.5 cm
Installation depth	11 cm
Net weight	0.09 kg
Gross weight	0.096 kg
IP Code	IP 20 / IP 44
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	7 W
Lumen	650 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR≤	22
LXXBXX data	L80B50
	•



## **Light Source**

798300	
Accessories	
1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005610	LED Driver , 200mA 10- W, Quick Connector
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1005612	NUMINOS® XS , diffuser
1005613	NUMINOS® XS , transparent diffuser
1005614	NUMINOS® XS , frosted diffuser
1005615	NUMINOS® XS , black diffuser

Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	29