




## **NUMINOS® XS**

## black / white recessed ceiling light, 2700K $55^{\circ}$

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® XS recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



## **TECHNICAL DATA**

| Item no.:                                | 1005506       |
|--|---------------|
| Secondary power / secondary volta-<br>ge | 200mA         |
| Height                                   | 4.5 cm        |
| Diameter                                 | 6.5 cm        |
| Installation diameter                    | 5.5 cm        |
| Installation depth                       | 11 cm         |
| Net weight                               | 0.09 kg       |
| Gross weight                             | 0.096 kg      |
| IP Code                                  | IP 20 / IP 44 |
| Safety class                             | III           |
| Impact resistance class                  | IK02          |
| Impact resistance                        | 0,2 Joule     |
| Assembly                                 | Recessed      |
| Assembly details                         | Ceiling       |
| Wattage                                  | 7 W           |
| Lumen                                    | 670 lm        |
| Colour temperature                       | 2700 Kelvin   |
| Beam angle                               | 55 °          |
| Color                                    | black         |
| CRI                                      | 90            |
| UGR≤                                     | 25            |
| LXXBXX data                              | L80B50        |
|  | •             |



## **Light Source**

| 798300      | F   |
|-------------|---|
| Accessories |   |
| 1005609     | LED Driver , 200mA 10W<br>PHASE, Quick Connector              |
| 1005610     | LED Driver , 200mA 10-<br>W, Quick Connector                  |
| 1005611     | LED Driver , 200mA<br>13,5W DALI dimmable,<br>Quick Connector |
| 1005612     | NUMINOS® XS , diffuser  |
| 1005613     | NUMINOS® XS , transparent diffuser                            |
| 1005614     | NUMINOS® XS , frosted diffuser                                |
| 1005615     | NUMINOS® XS , black diffuser                                  |

| Minimum ambient temperature | -20 °C |
|-----------------------------|--------|
| Maximum ambient temperature | 40 °C  |
| BIG WHITE Page              | 29     |