






## NUMINOS® XS

## black recessed ceiling light, 3000K $40^\circ$

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## **TECHNICAL DATA**

Item no.:	1005520	
Secondary power / secondary volta- ge	200mA	
Height	4.5 cm	
Diameter	6.5 cm	
Installation diameter	5.5 cm	
Installation depth	11 cm	
Net weight	0.09 kg	
Gross weight	0.096 kg	
IP Code	IP 20 / IP 44	
Safety class	111	
Impact resistance class	IK02	
Impact resistance	0,2 Joule	
Assembly	Recessed	
Assembly details	Ceiling	
Wattage	7 W	
Lumen	670 lm	
Colour temperature	3000 Kelvin	
Beam angle	40 °	
Color	black	
CRI	90	
UGR≤	22	
LXXBXX data	L80B50	
	•	



-20 °C 40 °C 29

## **Light Source**

798303	<b>F</b>	Minimum ambient temperature
Accessories	<u> </u>	Maximum ambient temperature
1005609	LED Driver , 200mA 10W PHASE, Quick Connector	BIG WHITE Page
1005610	LED Driver , 200mA 10- W, Quick Connector	
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector	
1005612	NUMINOS® XS , diffuser	
1005613	NUMINOS® XS , trans- parent diffuser	
1005614	NUMINOS® XS , frosted diffuser	
1005615	NUMINOS® XS , black diffuser	