




NUMINOS® XS

white recessed ceiling light, 3000K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| Item no.: | 1005533 |
|-------------------------------------|---------------|
| Secondary power / secondary voltage | 200mA |
| Height | 4.5 cm |
| Diameter | 6.5 cm |
| Installation diameter | 5.5 cm |
| Installation depth | 11 cm |
| Net weight | 0.09 kg |
| Gross weight | 0.096 kg |
| IP Code | IP 20 / IP 44 |
| Safety class | Ш |
| Impact resistance class | IK02 |
| Impact resistance | 0,2 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 7 W |
| Lumen | 720 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 55 ° |
| Color | white |
| CRI | 90 |
| UGR≤ | 25 |
| LXXBXX data | L80B50 |
| | |



Light Source

| 798303 | F |
|-------------|---|
| Accessories | |
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector |
| 1005610 | LED Driver , 200mA 10- W, Quick Connector |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1005615 | NUMINOS® XS , black diffuser |

| Minimum ambient temperature | -20 °C |
|-----------------------------|--------|
| Maximum ambient temperature | 40 °C |
| BIG WHITE Page | 29 |