


## NUMINOS® XS

## black / white recessed ceiling light, 4000K $40^\circ$

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINO-S® XS recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create unobtrustive, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



## **TECHNICAL DATA**

Item no.:	1005539
Secondary power / secondary volta- ge	200mA
Height	4.5 cm
Diameter	6.5 cm
Installation diameter	5.5 cm
Installation depth	11 cm
Net weight	0.09 kg
Gross weight	0.096 kg
IP Code	IP 20 / IP 44
Safety class	111
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	7 W
Lumen	730 lm
Colour temperature	4000 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR≤	22
LXXBXX data	L80B50



## Light Source

798305	Ê E	Minimum ambient temperate
Accessories		Maximum ambient temperat
1005609	LED Driver , 200mA 10W PHASE, Quick Connector	BIG WHITE Page
1005610	LED Driver , 200mA 10- W, Quick Connector	
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector	
1005612	NUMINOS® XS , diffuser	
1005613	NUMINOS® XS , trans- parent diffuser	
1005614	NUMINOS® XS , frosted diffuser	
1005615	NUMINOS® XS , black diffuser	

Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	29