




NUMINOS® MOVE XS

white / black recessed ceiling light, 2700K 20°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Like with the NUMINO-S® MOVE XS recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.:	1005562	
Secondary power / secondary volta- ge	200mA	
Height	5.5 cm	
Diameter	8 cm	
Installation diameter	6.8 cm	
Installation depth	11 cm	
Net weight	0.11 kg	
Gross weight	0.118 kg	
IP Code	IP 20	
Safety class	111	
Impact resistance class	IK02	
Impact resistance	0,2 Joule	
Assembly	Recessed	
Assembly details	Ceiling	
Wattage	7 W	
Lumen	640 lm	
Colour temperature	2700 Kelvin	
Beam angle	20 °	
Color	white	
CRI	90	
UGR≤	16	
LXXBXX data	L80B50	
	· · · · · · · · · · · · · · · · · · ·	



-20 °C 40 °C 39

Light Source

798300	‡ F	Minimum ambient temperature
Accessories	<u> </u>	Maximum ambient temperature
1005609	LED Driver , 200mA 10W PHASE, Quick Connector	BIG WHITE Page
1005610	LED Driver , 200mA 10- W, Quick Connector	
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector	
1005612	NUMINOS® XS , diffuser	
1005613	NUMINOS® XS , trans- parent diffuser	
1005614	NUMINOS® XS , frosted diffuser	
1005615	NUMINOS® XS , black diffuser	