




## NUMINOS® MOVE XS

## white recessed ceiling light, 2700K $55^\circ$

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® MOVE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## **TECHNICAL DATA**

Item no.:	1005569	
Secondary power / secondary volta- ge	200mA	
Height	5.5 cm	
Diameter	8 cm	
Installation diameter	6.8 cm	
Installation depth	11 cm	
Net weight	0.11 kg	
Gross weight	0.118 kg	
IP Code	IP 20	
Safety class	111	
Impact resistance class	IK02	
Impact resistance	0,2 Joule	
Assembly	Recessed	
Assembly details	Ceiling	
Wattage	7 W	
Lumen	670 lm	
Colour temperature	2700 Kelvin	
Beam angle	55 °	
Color	white	
CRI	90	
UGR≤	25	
LXXBXX data	L80B50	



-20 °C 40 °C 39

## Light Source

798300	‡ F	Minimum ambient temperature
Accessories	<u> </u>	Maximum ambient temperature
1005609	LED Driver , 200mA 10W PHASE, Quick Connector	BIG WHITE Page
1005610	LED Driver , 200mA 10- W, Quick Connector	
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector	
1005612	NUMINOS® XS , diffuser	
1005613	NUMINOS® XS , trans- parent diffuser	
1005614	NUMINOS® XS , frosted diffuser	
1005615	NUMINOS® XS , black diffuser	