




## NUMINOS® MOVE XS

## white / black recessed ceiling light, 3000K $20^\circ$

The NUMINOS light system from SLV skilfully combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® MOVE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## **TECHNICAL DATA**

Item no.:	1005580
Secondary power / secondary volta- ge	200mA
Height	5.5 cm
Diameter	8 cm
Installation diameter	6.8 cm
Installation depth	11 cm
Net weight	0.11 kg
Gross weight	0.118 kg
IP Code	IP 20
Safety class	
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	7 W
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR≤	16
LXXBXX data	L80B50



-20 °C 40 °C 39

## **Light Source**

798303	F	Minimum ambient temperature
Accessories	·	Maximum ambient temperature
1005609	LED Driver , 200mA 10W PHASE, Quick Connector	BIG WHITE Page
1005610	LED Driver , 200mA 10- W, Quick Connector	
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector	
1005612	NUMINOS® XS , diffuser	
1005613	NUMINOS® XS , trans- parent diffuser	
1005614	NUMINOS® XS , frosted diffuser	
1005615	NUMINOS® XS , black diffuser	