




## NUMINOS® MOVE S

white / chrome recessed ceiling light, 4000K 55°

The NUMINOS light system from SLV combines technology, design and functionality like no other. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Like with the NUMINOS® MOVE XS recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.:	1005608
Secondary power / secondary voltage	200mA
Height	5.5 cm
Diameter	8 cm
Installation diameter	6.8 cm
Installation depth	11 cm
Net weight	0.11 kg
Gross weight	0.118 kg
IP Code	IP 20
Safety class	III
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Wattage	7 W
Lumen	740 lm
Colour temperature	4000 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR ≤	25
LXXBXX data	L80B50

## Light Source

798305	
--------	---

## Accessories

1005609	LED Driver , 200mA 10W PHASE, Quick Connector
1005610	LED Driver , 200mA 10-W, Quick Connector
1005611	LED Driver , 200mA 13,5W DALI dimmable, Quick Connector
1005612	NUMINOS® XS , diffuser
1005613	NUMINOS® XS , transparent diffuser
1005614	NUMINOS® XS , frosted diffuser
1005615	NUMINOS® XS , black diffuser

Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	39