




NUMINOS® XL PHASE

white / black pendant light, 36W 3000K 60°

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® XL PHASE, which impresses as a pendant light with the best workmanship and lighting quality. The spotlight is ideal for targeted accent lighting or even illumination of larger areas. The pendant light can convince with a power consumption of 36 watts, luminous flux of 3210 lumens, colour temperature of 3000 Kelvin and a high colour reproduction index of over 90. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| | |
|-------------------------------------|------------------------|
| Item no.: | 1005716 |
| Number of different light outlets | 1 |
| Primary nominal voltage | 220-240V ~50/60Hz mA/V |
| Secondary power / secondary voltage | 900mA |
| Pendant length | 250 cm |
| Height | 25.8 cm |
| Diameter | 12 cm |
| Net weight | 1.745 kg |
| Gross weight | 1.867 kg |
| Safety class | I |
| Assembly | Surface |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Wattage | 36 W |
| Lumen | 3210 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 60 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 25 |
| BIG WHITE Page | 95 |

Light Source

| | |
|--------|---|
| 791823 |  |
|--------|---|

Accessories

| | |
|---------|-----------------------------------|
| 1006170 | NUMINOS® XL , white front ring |
|---------|-----------------------------------|