




## NUMINOS® GIMBLE XS

black / chrome recessed ceiling light, 4000K 20°

The NUMINOS light system from SLV skilfully combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE XS, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                     |             |
|-------------------------------------|-------------|
| Item no.:                           | 1005851     |
| Number of different light outlets   | 1           |
| Secondary power / secondary voltage | 200mA       |
| Height                              | 5.7 cm      |
| Diameter                            | 8 cm        |
| Installation diameter               | 6.8 cm      |
| Installation depth                  | 11 cm       |
| Net weight                          | 0.11 kg     |
| Gross weight                        | 0.118 kg    |
| Safety class                        | III         |
| Assembly                            | Recessed    |
| Assembly details                    | Ceiling     |
| Wattage                             | 7 W         |
| Lumen                               | 750 lm      |
| Colour temperature                  | 4000 Kelvin |
| Beam angle                          | 20 °        |
| Color                               | black       |
| CRI                                 | 90          |
| UGR ≤                               | 16          |
| BIG WHITE Page                      | 49          |

## Light Source

|        |   |
|--------|---|
| 798305 |  |
|--------|---|

## Accessories

|         |   |
|---------|---|
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector           |
| 1005610 | LED Driver , 200mA 10-W, Quick Connector                |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser                                  |
| 1005613 | NUMINOS® XS , transparent diffuser                      |
| 1005614 | NUMINOS® XS , frosted diffuser                          |
| 1005615 | NUMINOS® XS , black diffuser                            |
| 1006135 | Numinos® XS Mounting Frame , round 160/70mm black       |
| 1006136 | Numinos® XS Mounting Frame , round 160/70mm white       |
| 1006137 | Numinos® XS Mounting Frame , square 160/70mm black      |
| 1006138 | Numinos® XS Mounting Frame , square 160/70mm white      |