




NUMINOS® GIMBLE XS

white recessed ceiling light, 4000K 55°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® GIMBLE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| Item no.: | 1005865 |
|-------------------------------------|-------------|
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 200mA |
| Height | 5.7 cm |
| Diameter | 8 cm |
| Installation diameter | 6.8 cm |
| Installation depth | 11 cm |
| Net weight | 0.11 kg |
| Gross weight | 0.118 kg |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 7 W |
| Lumen | 740 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 55 ° |
| Color | white |
| CRI | 90 |
| UGR≤ | 25 |
| BIG WHITE Page | 49 |
| | • |



Light Source

| 798305 | Ĉ E |
|-------------|---|
| Accessories | |
| 1005609 | LED Driver , 200mA 10W PHASE, Quick Connector |
| 1005610 | LED Driver , 200mA 10- W, Quick Connector |
| 1005611 | LED Driver , 200mA 13,5W DALI dimmable, Quick Connector |
| 1005612 | NUMINOS® XS , diffuser |
| 1005613 | NUMINOS® XS , transparent diffuser |
| 1005614 | NUMINOS® XS , frosted diffuser |
| 1005615 | NUMINOS® XS , black diffuser |
| 1006135 | Numinos® XS Mounting Frame , round 160/70mm black |
| 1006136 | Numinos® XS Mounting Frame , round 160/70mm white |
| 1006137 | Numinos® XS Mounting Frame , square 160/70mm black |
| 1006138 | Numinos® XS Mounting Frame , square 160/70mm white |