


NUMINOS® GIMBLE S

black / chrome recessed ceiling light, 3000K 20°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® GIMBLE S recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that easy installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| | |
|-------------------------------------|-------------|
| Item no.: | 1005887 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 250mA |
| Height | 7 cm |
| Diameter | 10 cm |
| Installation diameter | 9 cm |
| Installation depth | 7 cm |
| Net weight | 0.18 kg |
| Gross weight | 0.193 kg |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 8.6 W |
| Lumen | 700 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 20 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 19 |
| BIG WHITE Page | 51 |

Light Source

| | |
|--------|---|
| 791815 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1004055 | LED driver , 6.5-10W 250mA PHASE |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1006139 | Numinos® S Mounting Frame , round 160/100mm black |
| 1006140 | Numinos® S Mounting Frame , round 160/100mm white |
| 1006141 | Numinos® S Mounting Frame , square 160/100mm black |
| 1006142 | Numinos® S Mounting Frame , square 160/100mm white |