




## NUMINOS® GIMBLE S

black / white recessed ceiling light, 3000K 55°

The NUMINOS light system from SLV perfectly combines function, design and technology. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE S recessed ceiling light, which impresses with its high-quality workmanship and light. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When do you choose NUMINOS® from SLV?



## TECHNICAL DATA

|                                     |             |
|-------------------------------------|-------------|
| Item no.:                           | 1005892     |
| Number of different light outlets   | 1           |
| Secondary power / secondary voltage | 250mA       |
| Height                              | 7 cm        |
| Diameter                            | 10 cm       |
| Installation diameter               | 9 cm        |
| Installation depth                  | 7 cm        |
| Net weight                          | 0.18 kg     |
| Gross weight                        | 0.193 kg    |
| Safety class                        | III         |
| Assembly                            | Recessed    |
| Assembly details                    | Ceiling     |
| Wattage                             | 8.6 W       |
| Lumen                               | 730 lm      |
| Colour temperature                  | 3000 Kelvin |
| Beam angle                          | 55 °        |
| Color                               | black       |
| CRI                                 | 90          |
| UGR ≤                               | 22          |
| BIG WHITE Page                      | 51          |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791815 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                          |
|---------|----------------------------------------------------------|
| 1004055 | LED driver , 6.5-10W<br>250mA PHASE                      |
| 1004058 | LED driver , 6.5-10W<br>250mA                            |
| 1004067 | LED driver , 15W 250mA<br>DALI                           |
| 1004786 | NUMINOS® S , diffuser<br>Ellipse                         |
| 1004787 | NUMINOS® S , diffuser<br>Prisma                          |
| 1004788 | NUMINOS® S , diffuser<br>Frosted                         |
| 1004789 | NUMINOS® S , diffuser<br>Wabe                            |
| 1006139 | Numinos® S Mounting<br>Frame , round<br>160/100mm black  |
| 1006140 | Numinos® S Mounting<br>Frame , round<br>160/100mm white  |
| 1006141 | Numinos® S Mounting<br>Frame , square<br>160/100mm black |
| 1006142 | Numinos® S Mounting<br>Frame , square<br>160/100mm white |