



NUMINOS® GIMBLE S

white / chrome recessed ceiling light, 4000K 40°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® GIMBLE S, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

| | |
|--|-------------|
| Item no.: | 1005917 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage ^e | 250mA |
| Height | 7 cm |
| Diameter | 10 cm |
| Installation diameter | 9 cm |
| Installation depth | 7 cm |
| Net weight | 0.18 kg |
| Gross weight | 0.193 kg |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 8.6 W |
| Lumen | 750 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 40 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 19 |
| BIG WHITE Page | 51 |

Light Source

| | |
|--------|---|
| 791831 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1004055 | LED driver , 6.5-10W 250mA PHASE |
| 1004058 | LED driver , 6.5-10W 250mA |
| 1004067 | LED driver , 15W 250mA DALI |
| 1004786 | NUMINOS® S , diffuser Ellipse |
| 1004787 | NUMINOS® S , diffuser Prisma |
| 1004788 | NUMINOS® S , diffuser Frosted |
| 1004789 | NUMINOS® S , diffuser Wabe |
| 1006139 | Numinos® S Mounting Frame , round 160/100mm black |
| 1006140 | Numinos® S Mounting Frame , round 160/100mm white |
| 1006141 | Numinos® S Mounting Frame , square 160/100mm black |
| 1006142 | Numinos® S Mounting Frame , square 160/100mm white |