




## NUMINOS® GIMBLE M

black / white recessed ceiling light, 4000K 55°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. The diverse downlights and spotlights make a thousand lighting design options possible. This also includes NUMINOS® GIMBLE M, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When will you choose SLV's modular variety?



## TECHNICAL DATA

|                                     |             |
|-------------------------------------|-------------|
| Item no.:                           | 1005964     |
| Number of different light outlets   | 1           |
| Secondary power / secondary voltage | 500mA       |
| Height                              | 9.5 cm      |
| Diameter                            | 13.5 cm     |
| Installation diameter               | 12 cm       |
| Installation depth                  | 9.5 cm      |
| Net weight                          | 0.42 kg     |
| Gross weight                        | 0.449 kg    |
| Safety class                        | III         |
| Assembly                            | Recessed    |
| Assembly details                    | Ceiling     |
| Wattage                             | 17.5 W      |
| Lumen                               | 1750 lm     |
| Colour temperature                  | 4000 Kelvin |
| Beam angle                          | 55 °        |
| Color                               | black       |
| CRI                                 | 90          |
| UGR ≤                               | 22          |
| BIG WHITE Page                      | 53          |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791825 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                          |
|---------|----------------------------------------------------------|
| 1004054 | LED driver , 20W 500mA<br>PHASE                          |
| 1004064 | LED driver , 21-29.5W<br>500/600/700mA                   |
| 1004069 | LED driver , 29W 500mA                                   |
| 1004790 | NUMINOS® M , diffuser<br>Ellipse                         |
| 1004791 | NUMINOS® M , diffuser<br>Prisma                          |
| 1004792 | NUMINOS® M , diffuser<br>Frosted                         |
| 1004793 | NUMINOS® M , diffuser<br>Wabe                            |
| 1006143 | Numinos® M Mounting<br>Frame , round<br>240/120mm black  |
| 1006144 | Numinos® M Mounting<br>Frame , round<br>240/120mm white  |
| 1006145 | Numinos® M Mounting<br>Frame , square<br>240/120mm black |
| 1006146 | Numinos® M Mounting<br>Frame , square<br>240/120mm white |