




## NUMINOS® GIMBLE L

white recessed ceiling light, 2700K 20°

The NUMINOS light system from SLV combines technology, design and functionality like no other. With different downlights and spotlights, you provide a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



## TECHNICAL DATA

Item no.:	1005985
Number of different light outlets	1
Secondary power / secondary voltage <sup>e</sup>	700mA
Height	11.5 cm
Diameter	16 cm
Installation diameter	14.5 cm
Installation depth	11.5 cm
Net weight	0.6 kg
Gross weight	0.642 kg
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	25.4 W
Lumen	2250 lm
Colour temperature	2700 Kelvin
Beam angle	20 °
Color	white
CRI	90
UGR ≤	22
BIG WHITE Page	55

## Light Source

791800	
--------	---

## Accessories

1004062	LED driver , 21-29.5W 500/600/700mA
1004065	LED driver , 30W 700mA
1004070	LED driver , 40W 700mA
1004794	NUMINOS® L , diffuser Ellipse
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1004797	NUMINOS® L , diffuser Wabe
1006147	Numinos® L Mounting Frame , round 240/150mm black
1006148	Numinos® L Mounting Frame , round 240/150mm white
1006149	Numinos® L Mounting Frame , square 240/150mm black
1006150	Numinos® L Mounting Frame , square 240/150mm white