




NUMINOS® GIMBLE L

black / chrome recessed ceiling light, 3000K 20°

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.:	1005995
Number of different light outlets	1
Secondary power / secondary voltage	700mA
Height	11.5 cm
Diameter	16 cm
Installation diameter	14.5 cm
Installation depth	11.5 cm
Net weight	0.6 kg
Gross weight	0.642 kg
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	25.4 W
Lumen	2200 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	22
BIG WHITE Page	55

Light Source

791822	
--------	---

Accessories

1004062	LED driver , 21-29.5W 500/600/700mA
1004065	LED driver , 30W 700mA
1004070	LED driver , 40W 700mA
1004794	NUMINOS® L , diffuser Ellipse
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1004797	NUMINOS® L , diffuser Wabe
1006147	Numinos® L Mounting Frame , round 240/150mm black
1006148	Numinos® L Mounting Frame , round 240/150mm white
1006149	Numinos® L Mounting Frame , square 240/150mm black
1006150	Numinos® L Mounting Frame , square 240/150mm white