




## NUMINOS® GIMBLE L

black recessed ceiling light, 3000K 40°

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. The various downlights and spotlights make a thousand lighting design options possible. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When do you choose NUMINOS ® from SLV?



## TECHNICAL DATA

|                                     |             |
|-------------------------------------|-------------|
| Item no.:                           | 1005996     |
| Number of different light outlets   | 1           |
| Secondary power / secondary voltage | 700mA       |
| Height                              | 11.5 cm     |
| Diameter                            | 16 cm       |
| Installation diameter               | 14.5 cm     |
| Installation depth                  | 11.5 cm     |
| Net weight                          | 0.6 kg      |
| Gross weight                        | 0.642 kg    |
| Safety class                        | III         |
| Assembly                            | Recessed    |
| Assembly details                    | Ceiling     |
| Wattage                             | 25.4 W      |
| Lumen                               | 2150 lm     |
| Colour temperature                  | 3000 Kelvin |
| Beam angle                          | 40 °        |
| Color                               | black       |
| CRI                                 | 90          |
| UGR ≤                               | 22          |
| BIG WHITE Page                      | 55          |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 791822 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                                          |
|---------|----------------------------------------------------------|
| 1004062 | LED driver , 21-29.5W<br>500/600/700mA                   |
| 1004065 | LED driver , 30W 700mA                                   |
| 1004070 | LED driver , 40W 700mA                                   |
| 1004794 | NUMINOS® L , diffuser<br>Ellipse                         |
| 1004795 | NUMINOS® L , diffuser<br>Prisma                          |
| 1004796 | NUMINOS® L , diffuser<br>Frosted                         |
| 1004797 | NUMINOS® L , diffuser<br>Wabe                            |
| 1006147 | Numinos® L Mounting<br>Frame , round<br>240/150mm black  |
| 1006148 | Numinos® L Mounting<br>Frame , round<br>240/150mm white  |
| 1006149 | Numinos® L Mounting<br>Frame , square<br>240/150mm black |
| 1006150 | Numinos® L Mounting<br>Frame , square<br>240/150mm white |