




## NUMINOS® GIMBLE L

## black / white recessed ceiling light, 4000K $55^\circ$

The NUMINOS light system from SLV combines technology, design and functionality like no other. With various downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® GIMBLE L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. In this way, you can create discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## **TECHNICAL DATA**

Item no.:	1006018
Number of different light outlets	1
Secondary power / secondary volta- ge	700mA
Height	11.5 cm
Diameter	16 cm
Installation diameter	14.5 cm
Installation depth	11.5 cm
Net weight	0.6 kg
Gross weight	0.642 kg
Safety class	111
Assembly	Recessed
Assembly details	Ceiling
Wattage	25.4 W
Lumen	2450 lm
Colour temperature	4000 Kelvin
Beam angle	55 °
Color	black
CRI	90
UGR≤	22
BIG WHITE Page	55



## Light Source

Î E
LED driver , 21-29.5W 500/600/700mA
LED driver , 30W 700mA
LED driver , 40W 700mA
NUMINOS® L , diffuser Ellipse
NUMINOS® L , diffuser Prisma
NUMINOS® L , diffuser Frosted
NUMINOS® L , diffuser Wabe
Numinos® L Mounting Frame , round 240/150mm black
Numinos® L Mounting Frame , round 240/150mm white
Numinos® L Mounting Frame , square 240/150mm black
Numinos® L Mounting Frame , square 240/150mm white