



NUMINOS® GIMBLE L

black / chrome recessed ceiling light, 4000K 55°

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. Installation is then done in no time at all. When will you choose SLV's modular variety?



TECHNICAL DATA

| | |
|-------------------------------------|-------------|
| Item no.: | 1006019 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 700mA |
| Height | 11.5 cm |
| Diameter | 16 cm |
| Installation diameter | 14.5 cm |
| Installation depth | 11.5 cm |
| Net weight | 0.6 kg |
| Gross weight | 0.642 kg |
| Safety class | III |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 25.4 W |
| Lumen | 2350 lm |
| Colour temperature | 4000 Kelvin |
| Beam angle | 55 ° |
| Color | black |
| CRI | 90 |
| UGR ≤ | 22 |
| BIG WHITE Page | 55 |

Light Source

| | |
|--------|---|
| 791825 |  |
|--------|---|

Accessories

| | |
|---------|--|
| 1004062 | LED driver , 21-29.5W 500/600/700mA |
| 1004065 | LED driver , 30W 700mA |
| 1004070 | LED driver , 40W 700mA |
| 1004794 | NUMINOS® L , diffuser Ellipse |
| 1004795 | NUMINOS® L , diffuser Prisma |
| 1004796 | NUMINOS® L , diffuser Frosted |
| 1004797 | NUMINOS® L , diffuser Wabe |
| 1006147 | Numinos® L Mounting Frame , round 240/150mm black |
| 1006148 | Numinos® L Mounting Frame , round 240/150mm white |
| 1006149 | Numinos® L Mounting Frame , square 240/150mm black |
| 1006150 | Numinos® L Mounting Frame , square 240/150mm white |