



NUMINOS® GIMBLE L

white / chrome recessed ceiling light, 4000K 55°

NUMINOS is the optimally coordinated light system from SLV that combines function, design and technology. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. Also with the NUMINOS® GIMBLE L recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. Installation is then done in no time at all. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.:	1006028
Number of different light outlets	1
Secondary power / secondary voltage	700mA
Height	11.5 cm
Diameter	16 cm
Installation diameter	14.5 cm
Installation depth	11.5 cm
Net weight	0.6 kg
Gross weight	0.642 kg
Safety class	III
Assembly	Recessed
Assembly details	Ceiling
Wattage	25.4 W
Lumen	2350 lm
Colour temperature	4000 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR ≤	22
BIG WHITE Page	55

Light Source

791825	
--------	---

Accessories

1004062	LED driver , 21-29.5W 500/600/700mA
1004065	LED driver , 30W 700mA
1004070	LED driver , 40W 700mA
1004794	NUMINOS® L , diffuser Ellipse
1004795	NUMINOS® L , diffuser Prisma
1004796	NUMINOS® L , diffuser Frosted
1004797	NUMINOS® L , diffuser Wabe
1006147	Numinos® L Mounting Frame , round 240/150mm black
1006148	Numinos® L Mounting Frame , round 240/150mm white
1006149	Numinos® L Mounting Frame , square 240/150mm black
1006150	Numinos® L Mounting Frame , square 240/150mm white