


## DL 126

**recessed fitting, LED SMD, 3000K, round, white, max. 3W, incl. leaf springs**

The DL 126 recessed fitting impresses with its low height and it is therefore ideal for use with low installation depths. The six long-life SMD LEDs with a total power output of 3W ensure that you have the necessary level of illumination. The recessed fitting is available with a shutter coloured white, chrome and brushed metal. A suitable 12V direct current power supply is needed for operation. This luminaire contains built-in warm-white LED lamps.



## TECHNICAL DATA

Item no.:	112221
Primary nominal voltage	12V mA/V
Height	1.6 cm
Diameter	6.5 cm
Installation diameter	5.7 cm
Installation depth	1.4 cm
Net weight	0.115 kg
Gross weight	0.14 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Wall
Lumen	170 lm
Colour temperature	3000 Kelvin
Beam angle	90 °
Color	white
CRI	80
LXXBXX data	L70B50
BIG WHITE Page	394

## Light Source

916556	
--------	---

## Accessories

112175	INSTALLATION FRAME , for DL 126 recessed fitting, triangle, brushed metal
112181	INSTALLATION FRAME , for DL 126 recessed fitting, round, white
112182	INSTALLATION FRAME , for DL 126 recessed fitting, round, chrome
112185	INSTALLATION FRAME , for DL 126 recessed fitting, round, brushed metal
470507	LED POWER SUPPLY , 12W, 12V