





VERLUX

recessed fitting, LED, 3000K, matt white, L/B/T
8.5/8.5/4.5 cm, 10W


The light, square recessed VERLUX fitting with a round cut-out is available in various wattages and sizes. The square recessed ceiling light is made of aluminium and comes in a white colour. The rigid Premium LED insert produces homogeneous base lighting thanks to its wide beam angle of 80°. The luminaire comes with a dimmable constant current driver and is ready for connection to the 230 V mains supply.



TECHNICAL DATA

Item no.:	112682
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Length	8.5 cm
Width	8.5 cm
Depth	4.5 cm
Installation diameter	7.5 cm
Installation depth	4.5 cm
Net weight	0.171 kg
Gross weight	0.238 kg
IP Code	IP 20
Safety class	II
Impact resistance class	IK02
Impact resistance	0,2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	11 W
Lumen	940 lm
Colour temperature	3000 Kelvin

Light Source

916585		Beam angle	80 °
		CRI	80
		LXXBXX data	L70B50
		BIG WHITE Page	393