





FRAME BASIC

recessed fitting, LED, 3000K, square, matt white, incl. leaf springs

With our FRAME series we offer you a lighting solution for recessed wall and ceiling installation with minimum space requirements. The LED version is equipped with a high-quality diode and available in either pure white or warm white light colour. To operate, the FRAME BASIC needs a suitable constant current driver rated at 350mA. The optional accessory includes a connector strip for simplified wiring in addition to the mounting box and flush-mount frame. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	113262
Secondary power / secondary voltage	350mA
Width	9 cm
Height	9 cm
Depth	6 cm
Installation length	7.5 cm
Installation width	7.5 cm
Installation depth	6.6 cm
Net weight	0.226 kg
Gross weight	0.286 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Wall
Wattage	1 W
Lumen	40 lm
Colour temperature	3000 Kelvin
Color	white
CRI	90
LXXBXX data	L70B50
BIG WHITE Page	409

Light Source

954799	
--------	---

Accessories

111850	MULTIWAY CONNECTOR , 3 outputs with two bridges, black, max. 350mA
111860	MULTIWAY CONNECTOR , 6 outputs with three bridges, black, max. 350mA
111861	CABLE EXTENSION , for items with a 350mA plug, 1 m
112780	FLUSH-MOUNTED , FRAME, for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
112781	MOUNTING BOX , for FRAME BASIC, FLAT FRAME BASIC, FLAT FRAME CURVE and FRAME CURVE
464107	LED DRIVER , 3VA, 350mA, with AMP plug, incl. strain relief