




NEW TRIA 68

recessed fitting, LED, 3000K, square, brushed aluminium, 38°, 12W, incl. driver, clip springs


The simplicity and effectiveness of the innovative NEW TRIA 68 recessed fitting is captivating. It is available in matt black, matt white or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.:	114396
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Length	8.2 cm
Width	8.2 cm
Height	4.5 cm
Installation diameter	6.8 cm
Installation depth	5 cm
Net weight	0.278 kg
Gross weight	0.33 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Wattage	11 W
Lumen	890 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	aluminium
CRI	80

Light Source

916451		LXXBXX data	L70B50
		BIG WHITE Page	361