





PATTa-I

recessed fitting, LED, 3000K, round, brushed aluminium, 38°, incl. driver

The innovative PATTa I recessed fitting is suitable for ceiling thicknesses of up to 25 mm. Rated IP65 it can be used outdoors or in damp areas. This set is available in matt black, matt white, or brushed aluminium as well as in round or square form. Equipped with a powerful, warm white premium COB LED in a rigid mount, as well as the dimmable LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.:	114426
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Height	4.5 cm
Diameter	8 cm
Installation diameter	6 cm
Installation depth	6 cm
Net weight	0.246 kg
Gross weight	0.299 kg
IP Code	IP 20 / IP 65
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Wattage	11 W
Lumen	910 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	aluminium
CRI	80
LXXBXX data	L70B50

Light Source

916451



BIG WHITE Page

707