


PATTA-F

recessed fitting, LED, 3000K, square, matt black, 38°, incl. driver


The innovative PATTA F recessed fitting is suitable for ceiling thicknesses of up to 20 mm. Rated IP65 it can be used outdoors or in damp areas. This set is available in matt black, white, or brushed aluminium as well as in round or square form. Equipped with a powerful, warm white premium COB LED in a tiltable mount, as well as dimmable LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.:	114450
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Length	8.3 cm
Width	8.3 cm
Height	6.2 cm
Installation diameter	7 cm
Installation depth	6 cm
Net weight	0.328 kg
Gross weight	0.396 kg
IP Code	IP 20 / IP 65
Safety class	II
Impact resistance class	IK02
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Wattage	11 W
Lumen	745 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black

Light Source

916451		CRI	80
		LXXBXX data	L70B50
		BIG WHITE Page	708