






KADUX 3 SET recessed fitting

triple-headed LED, 3000K, rectangular, matt black, 38° , 22W, incl. driver

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This LED set is multi-directional, allowing individual focus of the light beam. The KADUX 3 SET comes ready for direct connection to 230V mains and is available in matt black, matt white or brushed aluminium, as well as in single, double, or triple-headed variations.




TECHNICAL DATA

Item no.:	115720
Primary naminal voltage	220-240V ~50/60Hz mA/V
Primary nominal voltage	220-240V ~50/60H2 MAV V
Secondary power / secondary volta- ge	350mA
Length	21 cm
Width	9 cm
Height	8.5 cm
Installation length	20 cm
Installation width	8 cm
Installation depth	8 cm
Net weight	0.78 kg
Gross weight	0.863 kg
IP Code	IP 20
Safety class	Ш
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Wattage	20 W
Lumen	1920 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black



Light Source



CRI	80
LXXBXX data	L70B50
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
BIG WHITE Page	379