




KADUX 3 SET

recessed fitting, triple-headed LED, 3000K, rectangular, matt white, 38°, 3x9W, incl. driver

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This LED set is multi-directional, allowing individual focus of the light beam. The KADUX 3 SET comes ready for direct connection to 230V mains and is available in matt black, matt white or brushed aluminium, as well as in single, double, or triple-headed variations.



TECHNICAL DATA

Item no.:	115721
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	350mA
Length	21 cm
Width	9 cm
Height	8.5 cm
Installation length	20 cm
Installation width	8 cm
Installation depth	8 cm
Net weight	0.74 kg
Gross weight	0.808 kg
IP Code	IP 20
Safety class	II
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Wattage	20 W
Lumen	1920 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	white

Light Source

916451		CRI	80
		LXXBXX data	L70B50
		Minimum ambient temperature	-20 °C
		Maximum ambient temperature	35 °C
		BIG WHITE Page	379