





SUPROS 78

ceiling light, LED, 3000K, round, black, 60° lens

The SUPROS luminaire impresses with its multitude of possible applications, excellent LED technology and its harmonious design. With its very high luminous flux, the SUPROS product family is ideally suited to replace power-hungry, conventional lighting installations. The wide-area reflector included in the delivers can be replaced by reflectors with narrower beam angles which are optionally available. This can be done without the need for tools. With the factory-installed LED driver, all the luminaires in the series are suitable for direct connection to the 230V mains supply.



TECHNICAL DATA

Item no.:	116330
Number of different light outlets	1
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	250mA
Height	15.8 cm
Diameter	7.8 cm
Net weight	0.605 kg
Gross weight	0.664 kg
IP Code	IP 20
Safety class	I
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Wattage	12 W
Lumen	700 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	80
LXXBXX data	L70B50
BIG WHITE Page	271

Light Source

916364	
--------	---

Accessories

116302	LENS , for SUPROS 78, 20°
116304	LENS , for SUPROS 78, 40°