





DOWNUNDER PUR 80

recessed fitting, LED, 3000K, square, white, L/W/H 8/3.2/8 cm, incl. leaf springs

Aluminium recessed wall light of our DOWNUNDER 80 series. The not visibly mounted LED emits the light indirectly onto the surface to be illuminated. This guarantees glare-free illumination of walkways and much more. The DOWNUNDER PUR 80 recessed fitting is available in white colour version. To operate the recessed fitting, a suitable LED driver is required providing 350mA. A mounting frame for installation in masonry can be ordered from the accessory. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.:	151950
Secondary power / secondary voltage	350mA
Width	8 cm
Height	8 cm
Depth	3.2 cm
Installation length	7 cm
Installation width	6.5 cm
Installation depth	3.5 cm
Net weight	0.127 kg
Gross weight	0.174 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Wall
Wattage	3.6 W
Lumen	180 lm
Colour temperature	3000 Kelvin
Color	white
CRI	80
LXXBXX data	L70B50
BIG WHITE Page	412

Light Source

916412	
--------	---

Accessories

151960	FLUSH-MOUNTED FRAME , for DOWNUNDER PUR 80, L/H 14/14 cm
464109	LED DRIVER , 9W, 350-mA
464140	LED DRIVER , 10W, 350-mA, incl. strain relief, dimmable