





## KARPO

recessed fitting, single-headed, LED, 3000K, white, flat canopy, 7.5W

KARPO series lights are available in white and black. It has a spot in a cylindrical shape which can be individually aligned via the hinge on the flat canopy. The swivel and tilting range allows you to optimally light up the room. The integrated premium LEDs provide high energy efficiency. In addition, the luminaire has a high colour rendering index of over 90. To operate, the single-headed FRAME Spots needs a suitable constant current driver rated at 500mA.



## TECHNICAL DATA

Item no.:	152381
Secondary power / secondary voltage	500mA
Length	15.2 cm
Height	5.5 cm
Diameter	3 cm
Installation diameter	7 cm
Installation depth	2 cm
Net weight	0.177 kg
Gross weight	0.281 kg
IP Code	IP 20
Safety class	III
Assembly	Recessed
Assembly details	Ceiling, Wall
Wattage	7.5 W
Lumen	470 lm
Colour temperature	3000 Kelvin
Beam angle	40 °
Color	white
CRI	90
LXXBXX data	L70B50
Maximum ambient temperature	40 °C
BIG WHITE Page	400

## Light Source

916381	 An eco-label consisting of a yellow arrow pointing right, with the letter 'E' inside it. To the left of the arrow, the letters 'A' and 'G' are stacked vertically.
--------	--

## Accessories

464091	LED DRIVER , 9VA, 500-mA, incl. strain relief
--------	---