





## LOGS 40

outdoor floor stand, LED, 3000K, IP44, square, anthracite, L/W/H 13/8/39.5 cm, 8W

The indirect LED floor stand LOGS 40 is made from aluminium and equipped with a high-performance planar LED. Depending on the version various housing heights and colours are available. The required driver for direct connection to 230V mains supply is included in each package. For simplified mounting, a suitable earth-spike, screw set and junction box are available on accessory. In addition, the installation can be extended by wall lights of the series.



## TECHNICAL DATA

Item no.:	232115
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Width	13 cm
Height	39.5 cm
Depth	8 cm
Net weight	2.021 kg
Gross weight	2.714 kg
IP Code	IP 65
Safety class	I
Assembly	Surface
Assembly details	Ground
Wattage	9.5 W
Lumen	570 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50
Maximum ambient temperature	40 °C
BIG WHITE Page	517

## Light Source

916376	
--------	---

## Accessories

228730	CONNECTION BOX , 3-pin, IP68
228754	SCREW SET , stainless steel, M5, incl. plugs and washers.
231230	EARTH SPIKE , for GRA- FIT, RUSTY SLOT, LOGS floor stand, galva- nised steel, length 48cm
232119	CONCRETE ANCHOR SET , for LOGS floor stands, stainless steel