





H-POL

pathway and floor stand, single-headed, LED, 3000K, anthracite, L/W/H 16.5/16.5/66 cm

The H-POL SINGEL indirect radiating floor stand is made of aluminium and plastic. With protection class IP55, it is suitable for outdoor use. Thanks to the 8W LED, the luminaire is ideal for use as a pathway light. The product is designed for floor installation and is through-wireable. A large mounting pot is available for optimum mounting in the earth. Thanks to the built-in LED driver, it can be connected directly to the 230V mains supply.



TECHNICAL DATA

Item no.:	232165
Primary nominal voltage	100-277V ~50/60Hz mA/V
Secondary power / secondary voltage	500mA
Length	16.5 cm
Width	16.5 cm
Height	66 cm
Installation length	11.8 cm
Installation width	11.8 cm
Installation depth	10 cm
Net weight	2.358 kg
Gross weight	3.154 kg
IP Code	IP 55
Safety class	I
Assembly	Recessed
Assembly details	Ground, Ground with Acc.
Number of through-wires	18
Wattage	18 W
Lumen	700 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50

Light Source

916393	
--------	---

Accessories

232195	MOUNTING POT , for H-POL pathway and floor stand, anthracite
--------	--

Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
BIG WHITE Page	572