



## DOWNUNDER OUT LED S

outdoor recessed wall light, LED, 3000K, anthracite


The DOWNUNDER OUT LED S recessed wall light is made of aluminium, and outfitted with high output SMD LEDs that produce downward directed, glare-free light emission. Thanks to its IP55 protection class, the luminaire is suitable for outdoor use. The luminaire is connected directly to the 230V mains supply. A mounting pot is included in the delivery for simple assembly.



### TECHNICAL DATA

Item no.:	233605
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	300mA
Width	9 cm
Height	9 cm
Depth	5 cm
Installation length	8 cm
Installation width	7.5 cm
Installation depth	7 cm
Net weight	0.242 kg
Gross weight	0.284 kg
IP Code	IP 55
Safety class	I
Assembly	Recessed
Assembly details	Wall
Wattage	1.7 W
Lumen	25 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50
Minimum ambient temperature	-25 °C

## Light Source

916595	 A small icon for energy efficiency, showing a vertical bar with 'A' and 'G' on the left and a green arrow pointing right with a 'D' inside.	<b>Maximum ambient temperature</b>	50 °C
		<b>BIG WHITE Page</b>	701