





DOWNUNDER OUT LED M

outdoor recessed wall light, LED, 3000K, white


The DOWNUNDER OUT LED M recessed wall light is made of aluminium, and outfitted with high output SMD LEDs that produce downward directed, glare-free light emission. Thanks to its IP55 protection class, the luminaire is suitable for outdoor use. The luminaire is connected directly to the 230V mains supply. A mounting pot is included in the delivery for simple assembly.



TECHNICAL DATA

Item no.:	233621
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	300mA
Width	14 cm
Height	7 cm
Depth	5 cm
Installation length	12.6 cm
Installation width	5.8 cm
Installation depth	7 cm
Net weight	0.32 kg
Gross weight	0.359 kg
IP Code	IP 55
Safety class	I
Assembly	Recessed
Assembly details	Wall
Wattage	4 W
Lumen	155 lm
Colour temperature	3000 Kelvin
Color	white
CRI	80
LXXBXX data	L70B50
Minimum ambient temperature	-25 °C

Light Source

916417	 An energy label icon consisting of a yellow arrow pointing right, with the letters 'A', 'G', and 'E' stacked vertically inside it.	Maximum ambient temperature	50 °C
		BIG WHITE Page	701